

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17368**
T. 30 S., R. 5 W., Willamette Mer., Oregon

CHAINS

A twin madrone, 9 ins. diam., bears N. 1 1/2° W.,
20 lks. dist., with scribe marks 1/4 S29 BT
visible on open double blaze.

N. 87° 17' W., bet. secs. 29 and 32.

Descend 245 ft. over NW. slope, through heavy timber and
dense undergrowth.

6.30 Fence corner bears N., 10 lks. dist., with woven wire
fences extending S. and W.

8.95 Ravine, drains S. 55° W.; asc. 40 ft. over SE. slope.

20.15 Point for the W 1/16 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

W 1/16 $\frac{S\ 29}{S\ 32}$

1981

from which

A fir, 11 ins. diam., bears S. 59° E., 11 lks.
dist., mkd. W 1/16 S32 BT.

A fir, 10 ins. diam., bears N. 63 1/2° W., 29 lks.
dist., mkd. W 1/16 S29 BT.

Ascend 25 ft. over SE. slope.

20.20 Woven wire fence, extends N. and S.

21.35 Spur, slopes S. 45° W.; desc. 220 ft. over NW. slope.

28.60 Ravine, drains S. 40° W.; asc. 15 ft. over SE. slope.

29.30 Spur, slopes S. 40° W.; desc. 60 ft. over SW. slope.

32.05 Gravelled driveway, 20 lks. wide, bears N. 40° E. and
S. 40° W.

34.50 Dirt road, 20 lks. wide, bears N. 15° E. and S. 15° W.

36.15 Gravelled driveway, 20 lks. wide, bears N. 50° W. and
S. 50° E.

40.30 The cor. of secs. 29, 30, 31, and 32, perpetuated and
recorded by George J. Wenderoth, Deputy County Surveyor,
in 1946, subsequently perpetuated and recorded by Gary
Langlitz, Deputy County Surveyor, in 1979, monumented
with an iron post, 1 1/4 ins. diam., firmly set, projecting
1 in. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 5 W

S 30	S 29
S 31	S 32

1979