

County Surveyor's Record, Douglas County, Oregon

17369 Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Mer., Oregon

CHAINS

from which the remains of the original bearing trees

An oak, 27 ins. diam., bears S. 68° W., 70 lks.
dist., with axe marks visible on opened blaze.
(Record, S. 65° W.)

An oak, 21 ins. diam., bears N. 5° W., 12 lks.
dist., with axe marks visible on opened blaze.

and bearing trees mkd. by Wenderoth

An oak, 17 ins. diam., bears S. 55 1/2° E., 145 lks.
dist., with healed double blaze.

An oak, 34 ins. diam., bears S. 6 1/2° W., 143 lks.
dist., with healed double blaze.

An oak, 34 ins. diam., bears N. 44° W., 50 lks.
dist., with healed double blaze.

and bearing trees mkd. by Langlitz

A fir, 11 ins. diam., bears N. 80 1/2° E., 101 lks.
dist., with illegible scribe marks visible on
partially healed blaze.

A fir, 14 ins. diam., bears S. 89 1/2° W., 15 lks.
dist., with scribe marks T30S R5W S31 CS BT
visible on open double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, yew, oak, madrone, ash, cedar, alder,
chinquapin, and maple; undergrowth, poison oak, hazel,
fern, Oregon grape, arrowwood, huckleberry, salmonberry,
blackberry, and young timber.

N. 0° 13' W., bet. secs. 29 and 30.

Ascend 15 ft. over SW. slope, through scattering timber
and dense undergrowth, along N. and S. fence line.

3.45 Spur, slopes W.; desc. 130 ft. over NW. slope.


5.55 Fence corner, woven wire fences, extend N., S., and E.

15.65 Ravine, drains N. 75° W.; asc. 20 ft. over SW. slope.

16.30 Spur, slopes S. 85° W.; desc. 25 ft. over NW. slope.

19.84 Point for the S 1/16 sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.



from which

An oak, 10 ins. diam., bears N. 81 1/4° E., 21 1/2 lks.
dist., mkd. S 1/16 S29 BT.

A fir, 7 ins. diam., bears N. 56 1/2° W., 23 lks.
dist., mkd. S 1/16 S30 BT.