

# County Surveyor's Record, Douglas County, Oregon

17371

Subdivision of Section 29,  
T. 30 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**


From the 1/4 sec. cor. of secs. 29 and 32.

N. 1° 27' W., on the N. and S. center line of sec. 29.

Descend 120 ft. over NW. slope, through heavy timber and dense undergrowth.

- 7.25 Ravine, drains S. 25° W.; asc. 95 ft. over SE. slope.
- 15.90 Ravine, drains S. 40° E.; asc. 100 ft. over SW. slope.
- 18.65 Spur, slopes S. 70° E.; asc. 40 ft. along SE. slope.
- 20.14 Point for the center S 1/16 sec. cor. of sec. 29.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A madrone, 6 ins. diam., bears S. 8 1/2° E.,  
37 1/2 lks. dist., mkd. CS 1/16 S29 BT on bark.


A cedar, 10 ins. diam., bears S. 69° W.,  
51 lks. dist., mkd. CS 1/16 S29 BT.

Ascend 5 ft. over SE. slope.

- 20.35 Ridge, bears N. 50° E. and S. 50° W.; desc. 365 ft. over broken NW. slope.

- 40.28 Point for the center 1/4 sec. cor. of sec. 29, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A twin madrone, 6 ins. diam., bears S. 8 1/4° E.,  
35 1/2 lks. dist., mkd. C 1/4 S29 BT on bark.

A maple, 4 ins. diam., bears S. 69° W.,  
9 lks. dist., mkd. X BT.

Descend 45 ft. over NW. slope.

- 42.25 Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W.
- 45.70 Ravine, drains S. 75° W.; asc. 315 ft. over SE. slope.
- 56.35 Spur, slopes S. 45° W.; desc. 240 ft. over NW. slope.