

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 29,
T. 30 S., R. 5 W., Willamette Mer., Oregon

17372

CHAINS

- 67.80 Head of ravine, drains S. 70° W.; asc. 70 ft. over SW. slope.
- 72.10 Woven wire fence, extends N. 65° W. and S. 65° E.
- 73.40 Spur, slopes S. 75° W.; desc. 150 ft. over NW. slope.
- 80.64 The 1/4 sec. cor. of secs. 20 and 29, perpetuated and recorded by George C. Baker, Registered Land Surveyor, No. 77, in 1939, from original evidence no longer in existence, subsequently perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
1/4 $\frac{S\ 20}{S\ 29}$
R 5 W
1963

from which the remains of a bearing tree mkd. by Baker

A burned fir snag, size indeterminate, bears S. 22 1/2° W., 57 lks. dist., with illegible scribe marks visible on burned blaze.

and the remains of the bearing trees mkd. by Byron

A root hole, bears S. 23° E., 19 lks. dist., with downed madrone alongside, 10 ins. diam., with scribe marks 1/4 S29 CS BT visible on open double blaze.

A madrone snag, 22 ins. diam., bears N. 81° W., 30 1/2 lks. dist., with scribe marks 1/4 S20 CS BT visible on open double blaze.

and new bearing trees

A madrone, 8 ins. diam., bears N. 29° E., 25 1/2 lks. dist., mkd. 1/4 S20 BT on bark.

An oak, 5 ins. diam., bears S. 87° E., 31 lks. dist., mkd. X BT.

From the 1/4 sec. cor. of secs. 28 and 29.

N. 88° 05' W., on the E. and W. center line of sec. 29.

Descend 25 ft. over NW. slope, through heavy timber and dense undergrowth.

- 2.55 Creek, 2 lks. wide, course N. 60° E.; asc. 320 ft. over SE. slope.

- 19.00 Dirt road, 20 lks. wide, bears N. 30° E. and W.

- 26.00 Ridge, bears N. 75° E. and S. 75° W.; desc. 295 ft. over NW. slope.

- 27.10 Dirt road, 15 lks. wide, bears N. and S. 80° E., in curve.

- 35.40 Dirt road, 15 lks. wide, bears N. 50° E. and N. 80° E., in curve.