

County Surveyor's Record, Douglas County, Oregon

17373

Subdivision of Section 29,
T. 30 S., R. 5 W., Willamette Mer., Oregon

CHAINS	
40.53	The center 1/4 sec. cor. of sec. 29. Descend 135 ft. over NW. slope.
46.30	Dirt road, 15 lks. wide, bears N. 55° E. and S. 55° W.
47.20	Dirt road, 15 lks. wide, bears N. 25° W. and S. 25° E.
48.60	Creek, 1 lk. wide, course N. 40° W.; asc. 25 ft. over NE. slope.
50.85	Spur, slopes N. 5° W.; desc. 135 ft. over NW. slope.
60.24	Point for the center W 1/16 sec. cor. of sec. 29. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $C \frac{W \ 1/16}{S \ 29} C$ <p>1981</p> </div> from which A fir, 8 ins. diam., bears S. 51 1/2° W., 45 lks. dist., mkd. CW 1/16 S29 BT. A fir, 11 ins. diam., bears N. 29° W., 31 lks. dist., mkd. CW 1/16 S29 BT. Descend 50 ft. over NW. slope.
62.30	Power line, bears N. 45° E. and S. 45° W.
65.55	Ravine, drains S. 60° W.; asc. 50 ft. over SE. slope.
67.80	Spur, slopes S. 10° W.; desc. 25 ft. over SW. slope, also dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
68.40	Ravine, drains S. 20° E.; asc. 120 ft. over SE. slope.
79.95	The 1/4 sec. cor. of secs. 29 and 30.
From the S 1/16 sec. cor. of secs. 28 and 29. N. 89° 41' W., on the E. and W. center line of the SE 1/4 of sec. 29. Ascend 15 ft. along SE. slope, through heavy timber and dense undergrowth. 2.00 Spur, slopes S. 60° W.; desc. 90 ft. over SW. slope. 4.75 Ravine, drains S. 30° W.; asc. 15 ft. over SE. slope. 5.75 Spur, slopes S.; desc. 120 ft. over broken SW. slope. 13.85 Gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E. 15.00 Ravine, drains S. 30° E.; asc. 155 ft. over NE. slope. 19.90 Spur, slopes N. 30° E.; desc. 60 ft. along NW. slope. 24.05 Ravine, drains N. 40° E.; asc. 315 ft. over SE. slope. 39.67 The center S 1/16 sec. cor. of sec. 29.	