

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 29,
T. 30 S., R. 5 W., Willamette Mer., Oregon

17374

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 0° 52' W., on the N. and S. center line of the SW 1/4 of sec. 29.</p> <p>Ascend 45 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
0.35	Fence cor. bears W., 5 lks. dist., woven wire fences extend E. and S.
1.25	Spur, slopes S. 55° W.; desc. 35 ft. over NW. slope.
4.85	Head of ravine, drains S. 80° W.; asc. 90 ft. over SW. slope.
17.00	Spur, slopes S. 80° W.; desc. 75 ft. over NW. slope.
19.98	<p>Point for the SW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 29 1981</p> <p>from which</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears S. 1 3/4° W., 32 1/2 lks. dist., mkd. SW 1/16 S29 BT on bark.</p> <p style="padding-left: 40px;">A madrone, 4 ins. diam., bears N. 11 1/2° W., 30 lks. dist., mkd. X BT on bark.</p> <p>Descend 80 ft. over NW. slope.</p>
23.40	Ravine, drains S. 80° W.; asc. 45 ft. over SW. slope.
26.75	Spur, slopes N. 45° W.; desc. 280 ft. over broken NW. slope.
39.96	The center W 1/16 sec. cor. of sec. 29.
	<p>From the center S 1/16 sec. cor. of sec. 29.</p> <p>N. 87° 41' W., on the E. and W. center line of the SW 1/4 of sec. 29.</p> <p>Ascend 40 ft. over SE. slope, through heavy timber and dense undergrowth.</p>
2.25	Ridge, bears N. 80° E. and S. 40° W.; desc. 330 ft. over NW. slope.
19.92	<p>The SW 1/16 sec. cor. of sec. 29.</p> <p>Descend 390 ft. over broken NW. slope.</p>
39.50	Dirt road, 15 lks. wide, bears N. and S.
39.85	The S 1/16 sec. cor. of secs. 29 and 30.