

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17378**
T. 28 S., R. 4 W., Willamette Mer., Oregon

CHAINS

A root hole, bears N. 15° W., 36 lks. dist., with fragments of madrone wood alongside.

and bearing trees mkd. by Zirpel and Glenn

A fir, 12 ins. diam., bears N. 43 3/4° E., 85 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 21 1/4° E., 40 lks. dist., with healed blaze.

A cedar, 16 ins. diam., bears S. 30° W., 65 1/2 lks. dist., with healed blaze. (Record, 67 lks.)

A fir, 12 ins. diam., bears N. 72 1/4° W., 61 lks. dist., with healed blaze. (Record, 62 lks.)

N. 89° 21' W., bet. secs. 27 and 34, marking and blazing true line.

Ascend 15 ft. over SE. slope, through heavy timber and dense undergrowth.

0.80 Spur, slopes S.; desc. 240 ft. over broken SW. slope.

17.30 Ravine, drains S. 40° E.; asc. 110 ft. over SE. slope.

19.095 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 27}{S\ 34}$
1981

from which

A fir, 11 ins. diam., bears N. 22° W., 24 lks. dist., mkd. E 1/16 S27 BT.

A fir, 14 ins. diam., bears S. 29° W., 12 1/2 lks. dist., mkd. E 1/16 S34 BT.

Ascend 160 ft. over SE. slope.

23.55 Spur, slopes S.; desc. 260 ft. over SW. slope.

38.19 The 1/4 sec. cor. of secs. 27 and 34, perpetuated and recorded by G. G. Stewart, Deputy Douglas County Surveyor, in 1922, from original evidence no longer in existence, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 10 ins. above ground, from which the remains of bearing trees mkd. by Stewart

A sawed fir stump, 45 ins. diam., bears N. 88° E., 30 1/2 lks. dist., with scribe marks BT visible on opened blaze.

A madrone, 30 ins. diam., bears S. 11° W., 70 1/2 lks. dist., with axe marks visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.