

# County Surveyor's Record, Douglas County, Oregon

17379 Dependent Resurvey, Portion of Subdivisional Lines,  
T. 28 S., R. 4 W., Willamette Mer., Oregon

CHAINS

T 28 S    R 4 W  
1/4  $\frac{S 27}{S 34}$   
1981

from which new bearing trees

A cedar, 8 ins. diam., bears N. 45 1/4° E., 24 1/2 lks. dist., mkd. 1/4 S27 BT.

A fir, 16 ins. diam., bears S. 47 1/2° E., 52 lks. dist., mkd. 1/4 S34 BT.

Deposit the iron pipe alongside the iron post.

N. 89° 13' W., beginning new measurement.

Descend 145 ft. over broken SW. slope.

19.675

The W 1/16 sec. cor. of secs. 27 and 34, established and recorded by Robert W. Glaeser, Registered Land Surveyor, No. 1038, in 1980, and accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16  $\frac{S 27}{S 34}$   
1980

from which

A cedar, 10 ins. diam., bears N. 25 3/4° W., 38 lks. dist., mkd. W 1/16 S27 BT.

A fir, 12 ins. diam., bears S. 29 1/2° E., 19 1/2 lks. dist., mkd. W 1/16 S34 BT.

Deposit the iron pipe alongside the iron post.

N. 89° 13' W., beginning new measurement.

Descend 365 ft. over broken NW. slope.

19.675

The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 1/2 ins. diam.- firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 28 S    R 4 W  
 $\frac{S 28}{S 33}$  |  $\frac{S 27}{S 34}$   
1958

from which the remains of three original bearing trees

A root hole, bears S. 15° E., 104 lks. dist., with a down white oak lying alongside, 12 ins. diam.; no marks visible.

A sawed fir stump, 29 ins. diam., bears S. 50° W., 65 lks. dist.; no marks visible.

A sawed fir stump, 32 ins. diam., bears N. 70° W., 58 lks. dist.; no marks visible.