

County Surveyor's Record, Douglas County, Oregon

17381

Subdivision of Section 27,
T. 28 S., R. 4 W., Willamette Mer., Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FD. B. C. &
BT. - B. Shaw
7/17/92
C.S. 63/138*

T 28 S R 4 W

C 1/4 S 27

1981

from which

A cedar, 24 ins. diam., bears N. 73 1/2° E., 68 lks. dist., mkd. C 1/4 S27 BT.

A cedar, 19 ins. diam., bears S. 75° W., 72 lks. dist., mkd. C 1/4 S27 BT.

Ascend 325 ft. over SE. slope.

78.65

Top of ascent, slopes E.; desc. 15 ft. over NE. slope.

80.06

The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 28 S R 4 W

1/4 $\frac{S 22}{S 27}$

1958

from which the remains of an original bearing tree

A sawed fir stump, 36 ins. diam., bears S. 73 1/4° W., 42 lks. dist., with scribe marks SB visible on bark blaze. (Original record, S. 78° W.)

and a bearing tree mkd. by H. L. Eppstein, Douglas County Surveyor

A cedar, 25 ins. diam., bears S. 36 3/4° E., 59 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Zirpel and Glenn

A fir, 12 ins. diam., bears N. 61 1/4° W., 132 1/2 lks. dist., with healed blaze. (Record, 134 lks.)

A fir, 18 ins. diam., bears S. 21 1/4° W., 145 lks. dist., with healed blaze. (Record, 146 lks.)

and a new bearing tree

A fir, 6 ins. diam., bears N. 2° W., 29 lks. dist., mkd. 1/4 S22 BT.

Corner falls in swampy area.

From the 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 28 S R 4 W

1/4

S 27 | S 26

1958