

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 27,  
T. 28 S., R. 4 W., Willamette Mer., Oregon

17382

**CHAINS**

from which bearing trees mkd. by H. L. Eppstein, Douglas County Surveyor, in 1933 and described by Zirpel and Glenn in 1958

A fir, 30 ins. diam., bears S. 33 1/2° E., 45 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears S. 55° W., 6 lks. dist., with healed blaze.

S. 89° 15' W., on the E. and W. center line of sec. 27.

Descend 540 ft. over NW. slope, through heavy timber and dense undergrowth.

19.985

Point for the center E 1/16 sec. cor. of sec. 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C  $\frac{E\ 1/16}{S\ 27}$  C  
1981

from which

A fir, 14 ins. diam., bears N. 60 1/2° E., 25 lks. dist., mkd. CE 1/16 S27 BT.

A fir, 12 ins. diam., bears S. 21 1/2° E., 366 lks. mkd. CE 1/16 S27 BT.

Descend 60 ft. over NW. slope.

22.45

North Myrtle Creek, 12 lks. wide, course S. 70° W.; asc. 85 ft. over SE. slope.

38.30

Asphalt surfaced road, 30 lks. wide, bears N. 50° E. and S. 50° W.

39.97

The center 1/4 sec. cor. of sec. 27.

Descend 5 ft. over SW. slope.

42.15

Creek, 1 lk. wide, course S.; asc. 130 ft. over broken SE. slope.

59.25

Spur, slopes S. 30° E.; desc, 5 ft. over SW. slope.

59.595

Point for the center W 1/16 sec. cor. of sec. 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C  $\frac{W\ 1/16}{S\ 27}$  C  
1981

from which

A fir, 8 ins. diam., bears N. 67° W., 48 1/2 lks. dist., mkd. CW 1/16 S27 BT.

A fir, 8 ins. diam., bears S. 23 3/4° W., 60 lks. dist., mkd. CW 1/16 S27 BT.

Descend 5 ft. over SW. slope.

*FD. B.C. # BT's  
B. Shaner 7/17/72  
C.S. 63/138  
PER SHANER  
36.6 lks.*