

County Surveyor's Record, Douglas County, Oregon

17383

Subdivision of Sec. 27,
T. 28 S., R. 4 W., Willamette Mer., Oregon

CHAINS	
59.80	Creek, 1 lk. wide, course S. 30° E.; asc. 85 ft. over SE. slope.
61.65	Gravelled road, 25 lks. wide, bears N. 35° W. and S. 10° E.
73.00	Spur, slopes S. 5° E.; desc. 135 ft. over SW. slope.
79.22	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	T 28 S R 4 W 1/4 S 28 S 27 1958
	from which the remains of an original bearing tree
	A sawed fir stump, 30 ins. diam., bears N. 78° E., 18 lks. dist.; no marks visible.
	and the remains of bearing trees mkd. by J. W. Byron, Deputy Douglas County Surveyor, in 1957 and described by Zirpel and Glenn in 1958
	A cedar, 15 ins. diam., bears S. 78° E., 61 1/2 lks. dist., with healed blaze.
	A sawed fir stump, 16 ins. diam., bears S. 20 1/2° W., 42 lks. dist., with fragmentary scribe marks visible on decayed blaze.
	and a new bearing tree
	A fir, 7 ins. diam., bears N. 54 1/4° W., 41 lks. dist., mkd. 1/4 S28 BT.
From the E 1/16 sec. cor. of secs. 27 and 34.	
	N. 1° 21' E., on the N. and S. center line of the SE 1/4 of sec. 27.
	Ascend 115 ft. over SE. slope, through heavy timber and dense undergrowth.
6.65	Ridge, bears N. 65° E. and S. 65° W.; desc. 740 ft. over broken NW. slope.
41.27	The center E 1/16 sec. cor. of sec. 27.
From the W 1/16 sec. cor. of secs. 27 and 34.	
	N. 0° 08' E., on the N. and S. center line of the SW 1/4 of sec. 27.
	Ascend 30 ft. over SW. slope, through scattering timber and dense undergrowth.
1.25	Ridge, bears E. and W.; desc. 480 ft. over broken N. slope.
14.35	North Myrtle Creek, 10 lks. wide, course S. 70° W.; asc. 5 ft. over SW. slope.