

County Surveyor's Record, Douglas County, Oregon

17285

Subdivision of Sec. 27,
T. 28 S., R. 4 W., Willamette Mer., Oregon

CHAINS

9.20 North Myrtle Creek, 20 lks. wide, course S. 60° W.; desc. 5 ft. over SW. slope.

19.68 The SW 1/16 sec. cor. of sec. 27.


N. 89° 58' W., beginning new measurement.

Ascend 55 ft. over SE. slope.

10.80 Asphalt surfaced road, 30 lks. wide, bears N. 65° E. and S. 65° W.

18.35 Top of ascent, slopes S.; desc. 10 ft. over SW. slope.

19.65 The S 1/16 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which the remains of the bearing trees mkd. by Zirpel and Glenn

A fir, 17 ins. diam., bears N. 33 1/2° E., 29 lks. dist., with healed blaze.

A sawed fir stump, 22 ins. diam., bears N. 28 1/2° W., 39 1/2 lks. dist., with scribe marks BT visible on open blaze.

and a new bearing tree

A fir, 18 ins. diam., bears N. 71 1/2° W., 56 1/2 lks. dist., mkd. S 1/16 S28 BT.

From the center W 1/16 sec. cor. of sec. 27.


North, on the N. and S. center line of the NW 1/4 of sec. 27.

Ascend 365 ft. over SW. slope changing to SE. slope, through scattering timber and dense undergrowth.

0.20 SE. cor. of concrete pump house, 4 x 4 ft., bears W., 0.24 chs. dist.; long side bears N. 50° E. and S. 50° W.

37.25 Ridge, bears NE. and SW.; desc. 25 ft. over NW. slope.

39.26 The W 1/16 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Zirpel and Glenn

A chinquapin, 15 ins. diam., bears N. 67 3/4° E., 32 lks. dist., with healed blaze.

A chinquapin, 11 ins. diam., bears S. 49° W., 18 1/2 lks. dist., with healed blaze.