

County Surveyor's Record, Douglas County, Oregon

17389 Dependent Resurvey, Portion of the Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 28 S R 8 W

1/4 $\frac{S 23}{S 26}$

RLS 536 1973

from which the remains of bearing trees mkd. by Glenn S. Baughman, Registered Land Surveyor, No. 536, in 1973

A grand fir snag, 8 ins. diam., bears S. 50° W.,
26 lks. dist., with fragmentary scribe marks
visible on partially healed blaze.

A grand fir, 9 ins. diam., bears N. 65° W.,
13 1/2 lks. dist., with fragmentary scribe marks
visible on open blaze.

and a new bearing tree

A madrone, 16 ins. diam., bears S. 73 1/2° E.,
59 lks. dist., mkd. 1/4 S26 BT on bark.

S. 89° 46' W., bet. secs. 23 and 26, marking and blazing
the true line.

Descend over broken NW. slope, through heavy timber and
dense undergrowth.

8.05 Creek, 1 lk. wide, course N. 40° E.; asc. over NE. slope.

23.55 Spur, slopes N. 20° E.; desc. over NW. slope.

27.50 Ravine, drains N. 10° E.; asc. over broken E. slope.

40.00 The cor. of secs. 22, 23, 26, and 27, monumented with an
iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins.
above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S R 8 W

S 22 | S 23

S 27 | S 26

1957

from which the bearing trees mkd. by James W. Byron,
Deputy County Surveyor, in 1957

A cedar, 25 ins. diam., bears N. 18° E., 26 lks.
dist., with healed blaze.

A maple, 23 ins. diam., bears S. 36° E., 90 lks.
dist., with healed blaze.

A fir, 21 ins. diam., bears S. 55° W., 55 lks.
dist., with healed blaze.

A fir, 21 ins. diam., bears N. 89 1/2° W., 69 lks.
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, yew, maple, oak, alder, ash,
chinquapin, and madrone; undergrowth, poison oak, salal,