


# County Surveyor's Record, Douglas County, Oregon

17391

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

- 7.75 Spur, slopes N. 85° E.; desc. over NE. slope.
- 9.00 Creek, 1 lk. wide, course S. 80° E.; asc. over SE. slope.
- 17.25 Spur, slopes N. 60° E.; desc. over NE. slope.
- 19.96 The N 1/16 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Jelley

A chinquapin, 9 ins. diam., bears S. 79 1/2° E.,  
33 lks. dist., with scribe marks N 1/16 S23 BT  
visible on open blaze.

A grand fir, 14 ins. diam., bears N. 63° W.,  
32 1/2 lks. dist., with healed blaze.

N. 0° 11' W., beginning new measurement.

Descend over NE. slope, changing to NW. slope.

- 11.35 Tenmile Creek, 10 lks. wide, course N. 65° E.; asc. over SE. slope.

- 20.04 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



1957

from which bearing trees mkd. by James W. Byron, Deputy  
County Surveyor, in 1957

A black walnut, 38 ins. diam., bears N. 76° E.,  
719 lks. dist., with healed blaze.

A black oak, 43 ins. diam., bears S. 37 1/2° E.,  
412 lks. dist., with healed blaze.

A fir, 43 ins. diam., bears S. 23° W.,  
534 lks. dist., with healed blaze.

A white oak, 43 ins. diam., bears N. 53° W.,  
208 lks. dist., with healed blaze.