

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 21,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

17396

CHAINS	
	T 28 S R 8 W $1/4 \frac{S 21}{S 28}$ 1973
	from which bearing trees mkd. during the 1973 resurvey A fir, 15 ins. diam., bears S. 37 1/2° E., 82 lks. dist., with healed blaze. A fir, 12 ins. diam., bears N. 17° W., 43 lks. dist., with healed blaze. N. 0° 03' W., on the N. and S. center line of sec. 21. Descend over NE. slope, through moderate timber and dense undergrowth.
5.80	Creek, 5 lks. wide, course S. 80° E.; asc. over broken SE. slope.
29.20	Spur, slopes S. 60° E.; desc. over NE. slope.
40.38	Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 28 S R 8 W C 1/4 S 21 1980
	from which A cedar, 8 ins. diam., bears N. 22° E., 13 lks. dist., mkd. C 1/4 S21 BT. A fir, 6 ins. diam., bears S. 36 1/4° W., 22 lks. dist., mkd. C 1/4 S21 BT. Descend over NE. slope.
46.25	Creek, 2 lks. wide, course N. 50° E.; asc. over SE. slope.
51.00	Spur, slopes S. 50° E.; desc. over NE. slope.
55.35	Creek, 5 lks. wide, course N. 80° E.; asc. over SE. slope.
60.30	Ridge, bears N. 70° W. and S. 65° E.; desc. over broken NE. slope.
62.50	Dirt road, 20 lks. wide, bears N. 10° W. and S. 10° E.
79.20	Creek, 5 lks. wide, course S. 70° E.; asc. over SE. slope.
80.82	The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.