

# County Surveyor's Record, Douglas County, Oregon

17397

Subdivision of Section 21,  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 28 S    R 8 W  
1/4  $\frac{S 16}{S 21}$

1975

from which bearing trees mkd. by Jelley

A fir, 16 ins. diam., bears S. 62° W., 31 1/2 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 82° W., 45 1/2 lks. dist., with healed blaze.

From the 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 28 S    R 8 W  
1/4  
S 21 | S 22

1973

from which bearing trees mkd. during the 1973 resurvey

A fir, 18 ins. diam., bears N. 66° E., 38 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 49° W., 70 lks. dist., with healed blaze.

S. 89° 13' W., on the E. and W. center line of sec. 21.

Descend over SW. slope, through heavy timber and dense undergrowth.

0.70 Creek, 1 lk. wide, course S. 25° E.; asc. over broken SE. slope, changing to NE. slope.

40.36 The center 1/4 sec. cor. of sec. 21.

Ascend over broken NE. slope.

46.45 Spur, slopes N.; desc. over NW. slope.

49.50 Creek, 8 lks. wide, course N. 60° E.; asc. over SE. slope.

60.52 Point for the center W 1/16 sec. cor. of sec. 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C  $\frac{W 1/16}{S 21}$  C

1980

from which

A fir, 6 ins. diam., bears N. 23° E., 15 1/2 lks. dist., mkd. CW 1/16 S21 BT.

A fir, 8 ins. diam., bears S. 9 1/2° E., 58 lks. dist., mkd. CW 1/16 S21 BT.

Ascend over SE. slope.