


# County Surveyor's Record, Douglas County, Oregon

17399

Subdivision of Section 23,  
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	N. 0° 04' W., on the N. and S. center line of sec. 23. Descend over broken NW. slope.
15.00	Head of ravine, drains N. 70° W.; asc. over SW. slope.
18.85	Spur, slopes N. 35° W.; desc. over broken NE. slope.
40.06	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E. and W. center line.  Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 28 S    R 8 W  C 1/4    S 23  1982
	from which
	A grand fir, 8 ins. diam., bears S. 35 1/2° E., 34 1/2 lks. dist., mkd. C 1/4 S23 BT.
	A grand fir, 10 ins. diam., bears N. 38 1/4° W., 20 lks. dist., mkd. C 1/4 S23 BT.
	From this point, a point established and recorded by Glenn S. Baughman, Registered Land Surveyor, No. 536, in 1973, bears S. 11° 47' W., 0.142 chs. dist., as determined from bearing trees mkd. by Baughman
	A fir, 11 ins. diam., bears S. 9° E., 10 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	A grand fir, 10 ins. diam., bears N. 14° W., 31 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	Descend over NE. slope.
40.25	Barbed wire fence, extends E. and W.
47.75	Tenmile Creek, 30 lks. wide, course S. 65° E.; asc. over broken SW. slope.
59.50	Paved road, 35 lks. wide, bears N. 35° W. and S. 35° E.
60.00	Point for the center N 1/16 sec. cor. of sec. 23.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	
	1982
	from which
	A cedar, 17 ins. diam., bears S. 38 1/2° E., 19 lks. dist., mkd. CN 1/16 S23 BT.