

County Surveyor's Record, Douglas County, Oregon

17405

T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of portions of the south and west boundaries, and subdivisional lines, township 33 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The south two miles of the west boundary and the south boundary of the township, and a portion of the subdivisional lines were surveyed by William H. Byars, U.S. Deputy Surveyor, in 1882.

The survey of the west boundary of the township and subdivisional lines was completed by Oscar F. Thiel, U.S. Deputy Surveyor, in 1901.

The west boundary of the township was resurveyed by Norman D. Price, U.S. Surveyor, and Ira F. Shaffner, U.S. Transitman, in 1919. Price and Shaffner established section corners and 1/4 section corners for T. 33 S., R. 8 W. only, on the range line and changed the Byars and Thiel corners to corners of minimum control.

In 1917 Quintin Campbell, Thos. D. Daley, Gerald A. Sorrels, and Ira F. Shaffner, U.S. Transitmen, and Norman D. Price, U.S. Surveyor, resurveyed the south boundary of T. 33 S., R. 8 W.

Portions of the south boundary and subdivisional lines were resurveyed and section 33 was subdivided by Hans W. Thielsen, Cadastral Surveyor, in 1957.

Portions of the south boundary and subdivisional lines were resurveyed, section 1 was subdivided, and certain original corner points were remonumented without survey by Rollin D. Aanrud, John M. Jelley, and Lynn M. Roseberry, Cadastral Surveyors, in 1969-70.

A portion of the subdivisional lines was resurveyed by Larry D. Evans, Cadastral Surveyor, in 1973.

A portion of the subdivisional lines was resurveyed and section 3 was subdivided by Rollin D. Aanrud and Lynn M. Roseberry, Cadastral Surveyors, in 1975.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 16, 1981, for Group Number 1050, Oregon.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice. Only lines bounding or crossing public lands were blazed.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.