

# County Surveyor's Record, Douglas County, Oregon

17406

T. 33 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

The geographic position of the corner of sections 5, 6, 31, and 32, on the south boundary of the township, as scaled from the "GALICE, OREG.", topographic map, published by the United States Geological Survey in 1946, is:

Latitude 42° 39.1' N. Longitude 123° 33.7' W.

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars, in 1882,  
the resurvey by Hans W. Thielsen, in 1957, and the  
resurvey by Rollin D. Aanrud, John M. Jelley,  
and Lynn M. Roseberry, in 1969-70.)

Beginning at the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T	33	S	R	7	W
	S	31		S	32
	S	6		S	5
	T	34	S		
1969					

from which the remaining original bearing tree

A fir, 40 ins. diam., bears N. 10° W., 94 lks. dist., with healed blaze. (Original record, 96 lks.)

and bearing trees mkd. by Marvin C. Ramsey, Registered Land Surveyor, No. 404, in 1958

A fir, 13 ins. diam., bears N. 32° E., 12 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears S. 71 1/4° E., 33 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears S. 52 3/4° W., 61 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears N. 45° W., 46 lks. dist., with healed blaze.

S. 89° 44' W., bet. secs. 6 and 31, marking and blazing the true line.

Descend 35 ft. along N. slope, through heavy timber and dense undergrowth.

6.00 Abandoned dirt road, 20 lks. wide, bears N. 45° W. and S. 45° E.

8.30 Bottom of descent, drains N.; asc. 145 ft. over NE. slope.

15.30 Spur, slopes N.; desc. 40 ft. along N. slope.

20.25 Point for the E. 1/16 sec. cor. of secs. 6 and 31.