

County Surveyor's Record, Douglas County, Oregon

17411

Dependent Resurvey, Portion of W. Bdy.,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A madrone, 12 ins. diam., bears N. 53° W., 33 lks. dist., with illegible scribe marks visible on decayed double blaze. (Record, N. 52° W., 27 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground; with brass cap mkd.

T 33 S	T 33 S
R 8 W	S 18
S 13	S 19
	R 7 W
	1981

Deposit the corner stone alongside the iron post.

From this point, the cor. of secs. 13 and 24 only, on the E. bdy. of T. 33 S., R. 8 W., bears S. 0° 37' W., 1.80 chs. dist., monumented with the original granite stone, 20 x 14 x 10 ins., firmly set, 10 ins. in the ground, mkd. with 3 notches on the N. and S. edges, from which the remaining original bearing tree

A madrone, 10 ins. diam., bears N. 40° W., 55 lks. dist., with a healed blaze.

N. 0° 58' E., on the W. bdy. of sec. 18.

Ascend 175 ft. along broken E. slope, through heavy timber and dense undergrowth.

13.20 Trail, 5 lks. wide, bears N. 30° E. and S. 30° W.

16.90 Trail, 5 lks. wide, bears N. 30° W. and S. 30° E.

17.00 Creek, 3 lks. wide, course S. 30° E.; asc. 150 ft. over SE. slope.

20.03 Point for the S. 1/16 sec. cor. of sec. 18 only, on the W. bdy. of the Tp.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

	S 1/16
	S 18
	1981

from which

A fir, 4 ins. diam., bears N. 62 1/2° E., 24 lks. dist., mkd. X at breast height and BT at base.

A fir, 8 ins. diam., bears S. 33 1/2° E., 39 lks. dist., mkd. S 1/16 S18 BT.

Ascend 400 ft. along broken E. slope.

37.90 Spur, slopes E.; desc. 10 ft. over NE. slope.

38.18 Point for the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of T. 33 S., R. 8 W., at proportionate dist.; there is no remaining evidence of the original corner.