

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17414**  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 7 ins. diam., bears S. 72 1/2° W., 64 1/2 lks. dist., mkd. 1/4 S10 BT.

Descend 155 ft. over NW. slope.

50.20 Spur, slopes NW.; desc. 685 ft. over broken NW. slope.

79.35 Creek, 1 lk. wide, course N. 75° W.; desc. 5 ft. along W. slope.

79.92 The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 33 S	R 7 W
S 3	S 2
S 10	S 11

1968

from which the remains of the original bearing trees

A sawed maple stump, 15 ins. diam., bears N. 33° E., 87 lks. dist., with healed blaze. (Record, N. 32° E., 92 lks.)

A sawed fir stump, 32 ins. diam., bears S. 63 3/4° E., 29 1/2 lks. dist., with illegible scribe marks visible on open burned blaze. (Record, S. 58° E., 28 lks.)

A cedar, 25 ins. diam., bears N. 70° W., 8 lks. dist., no marks visible on decayed blaze. This tree rescribed by the County Surveyor's Office with scribe marks T33S R7W S3 CS BT visible on partly healed blaze.

and bearing trees mkd. by the County Surveyor's Office

A fir, 36 ins. diam., bears N. 3° E., 134 lks. dist., with healed blaze.

A sawed fir stump, 40 ins. diam., bears S. 89 1/2° E., 20 lks. dist., with scribe marks T33 visible on partly healed blaze.

and new bearing trees

A fir, 4 ins. diam., bears S. 35 1/2° E., 22 lks. dist., mkd. T33S R7W S11 BT.

An alder, 10 ins. diam., bears S. 58 1/2° W., 24 lks. dist., mkd. T33S R7W S10 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, chinquapin, maple, and alder; undergrowth, poison oak, manzanita, hazel, vine maple, salal, and Oregon grape.

From the cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by Max H. Hull, Registered Land Surveyor, No. 901, in 1973, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with plastic cap mkd. Hull RS 901, from which the remains of the original bearing trees