

County Surveyor's Record, Douglas County, Oregon

17415

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 62° E., 21 lks. dist.,
alongside of which is lying a fir, 70 ins.
diam., no marks visible.

A maple, 15 ins. diam., bears S. 63° W., 47 lks.
dist., with healed blaze.

and bearing trees mkd. by Hull

A chinquapin, 24 ins. diam., bears N. 37 1/2° E.,
39 1/2 lks. dist., with scribe marks S15 RS 901
BT visible on partly healed blaze.

A tanoak, 13 ins. diam., bears S. 29° E., 56 lks.
dist., with scribe marks RS 901 visible on
partly healed blaze.

A maple, 11 ins. diam., bears N. 49° W., 51 1/2 lks.
dist., with scribe marks RS 901 visible on
partly healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, directly over the iron rod, with brass cap
mkd.

T 33 S	R 7 W
S 16	S 15
S 21	S 22
1981	

N. 0° 02' E., bet. secs. 15 and 16.

Descend 25 ft. over NE. slope, through heavy timber and
dense undergrowth.

0.90 Creek, 5 lks. wide, course S. 65° E.; asc. 580 ft. over
SW. slope.

5.15 Dirt road, 20 lks. wide, bears N. 60° W. and S. 60° E.

20.00 Spur, slopes SE.; desc. 150 ft. along E. slope, changing
to NE. slope.

27.80 Dirt road, 15 lks. wide, bears N. 55° W. and S. 55° E.

38.90 The 1/4 sec. cor. of secs. 15 and 16, perpetuated and re-
corded by Max H. Hull, Registered Land Surveyor, No. 901,
in 1973, monumented with an iron rod, 5/8 in. diam.,
firmly set, projecting 2 ins. above ground, with plastic
cap mkd. Hull RS 901, from which the remains of the orig-
inal bearing trees

A root hole, bears S. 53° E., 26 lks. dist.

A decayed fir stump, size indeterminate, bears
S. 70° W., 31 lks. dist., no marks visible.

and bearing trees mkd. by Hull

A fir, 13 ins. diam., bears N. 6° E., 71 lks.
dist., with healed blaze.