

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17416**
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 15 ins. diam., bears N. 48° W., 17 lks. dist., with illegible scribe marks visible on partly healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 33 S R 7 W
 1/4
 S 16 | S 15
 1981

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, cedar, oak, madrone, chinquapin, alder, and maple; undergrowth, poison oak, manzanita, vine maple, hazel, salal, and Oregon grape.

From the 1/4 sec. cor. of secs. 10 and 15, perpetuated and recorded by the Douglas County Surveyor's Office in 1968, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR
T 33 S R 7 W
 DOUG
 1/4 S 10
 S 15
 1968

from which the remaining original bearing tree

A fir, 58 ins. diam., bears N. 33° W., 24 lks. dist., with scribe marks 1/BT visible on bark blaze. This tree was remarked by the County Surveyor's Office, and the blaze is healed. (Record, 20 lks.)

and a bearing tree mkd. by the County Surveyor's Office

A fir, 25 ins. diam., bears S. 58° W., 112 1/2 lks. dist., with scribe mark S visible on partly healed blaze.

S. 89° 59' W., bet. secs. 10 and 15, marking and blazing the true line.

Descend 50 ft. over NW. slope, through heavy timber and dense undergrowth.

3.40 Ravine, drains N.; asc. 50 ft. over NE. slope.

6.55 Spur, slopes N.; asc. 10 ft. along N. slope.

10.90 Ridge, bears NW. and SE., also dirt toad, 15 lks. wide, bears same; desc. 240 ft. over SW. slope.

19.67 Point for the W 1/16 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.