

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17418**
 T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A madrone, 18 lks. dist., bears N. 30° W., 130 lks. dist., no marks visible on opened, decayed, double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T 33 S R 7 W
 1/4
 S 9 | S 10
 1981

from which new bearing trees

A sugar pine, 21 ins. diam., bears N. 38 3/4° E., 67 lks. dist., mkd. 1/4 S10 BT.

A fir, 12 ins. diam., bears N. 47 1/2° W., 54 1/2 lks. dist., mkd. 1/4 S9 BT.

N. 0° 15' W., bet. secs. 9 and 10.

Descend 270 ft. over NW. slope, through heavy timber and dense undergrowth.

7.10 Perkins Creek, 6 lks. wide, course N. 70° E.; asc. 185 ft. over SE. slope.

14.00 Top of ascent, slopes E.; desc. 250 ft. over broken NE. slope.

31.60 Creek, 5 lks. wide, course E.; asc. 300 ft. over SE. slope.

38.21 The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 33 S R 7 W
 S 4 | S 3
 S 9 | S 10
 1975

from which the remaining original bearing tree

A fir, 36 ins. diam., bears N. 80° W., 10 lks. dist., with illegible scribe marks visible on a burned blaze.

and the remains of a bearing tree mkd. by Norman D. Price, Registered Land Surveyor, No. 33, and described in the 1975 resurvey record

A root hole, bears S. 26° W., 27 lks. dist., alongside of which is lying a shattered live oak, size indeterminate, with scribe marks T33S R7W S9 RS 33 BT visible on an open blaze.

and bearing trees mkd. by Aanrud and Roseberry

A tanoak snag, 7 ins. diam., bears S. 46 1/4° E., 40 lks. dist., no marks visible on partly healed blaze.

A fir, 25 ins. diam., bears S. 43 1/2° W., 91 lks. dist., with scribe marks T33S R7W S9 BT visible on open blaze. (Record, S. 49 1/2° W.)