

County Surveyor's Record, Douglas County, Oregon

17419

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and new bearing trees

A madrone, 6 ins. diam., bears N. 45° E., 66 1/2 lks. dist., mkd. T33S R7W S3 BT.

A madrone, 6 ins. diam., bears S. 11° E., 44 1/2 lks. dist., mkd. T33S R7W S10 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, and chinquapin; undergrowth, poison oak, manzanita, hazel, huckleberry, salal, Oregon grape, and young timber.

From the cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 33 S	R 7 W
S 21	S 22
S 28	S 27
1970	

from which the remains of the original bearing trees

A root hole, bears S. 18° W., 110 lks. dist., alongside of which is lying a decayed ponderosa pine, 30 ins. diam., no marks visible. (Original record, S. 25° W.)

A ponderosa pine, 24 ins. diam., bears N. 37° W., 100 lks. dist., with illegible scribe marks visible on opened blaze. (Original record, N. 36° W.)

and bearing trees mkd. by Jelley, Aanrud, and Roseberry

A fir, 22 ins. diam., bears N. 28° E., 26 lks. dist., with pitched over blaze.

A fir, 8 ins. diam., bears S. 43 1/2° E., 40 lks. dist., with healed blaze.

A madrone, 15 ins. diam., bears S. 56° W., 36 1/2 lks. dist., with scribe marks T33S R7W S28 BT visible on partly healed blaze.

S. 89° 49' W., bet. secs. 21 and 28.

Descend 100 ft. over W. slope, through heavy timber and dense undergrowth.

6.20 Ravine, drains SW.; asc. 75 ft. over SE. slope.

9.70 Spur, slopes S.; desc. 100 ft. over SW. slope.

23.00 Creek, 9 lks. wide, course S. 30° E.; asc. 575 ft. over NE. slope.

40.44 The 1/4 sec. cor. of secs. 21 and 28, reestablished at proportionate distance and recorded by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1981, and accepted as the best available evidence of the position of the original cor., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd. T33S R7W 1/4 S21 S28 LS 498 1981, from which bearing trees mkd. by Johnstone