

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17420
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 4 ins. diam., bears S. 44 1/2° E., 25 lks. dist., with scribe marks 1/4 SFC 28 BT visible on open blaze.

A fir, 14 ins. diam., bears N. 28 1/2° W., 8 1/2 lks. dist., with scribe marks 1/4 S21 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 33 S R 7 W
 1/4 $\frac{S\ 21}{S\ 28}$
 1981

S. 89° 49' W., beginning new measurement.

Ascend 20 ft. over E. slope.

1.20 Spur ridge, bears NW. and SE., slopes SE.; asc. 205 ft. along broken S. slope.

26.10 Ridge, bears N. and S., also junction of dirt roads, 20 lks. wide, bearing E., W., and S., curving NE. and NW.; desc. 465 ft. over W. slope.

40.44 The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by the Josephine County Surveyor's Office, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR
T 33 S R 7 W
 20 | 21
 29 | 28
 1976

from which the remaining original bearing trees

A live oak, 14 ins. diam., bears N. 71° E., 26 lks. dist., with scribe marks BT visible on opened blaze. (Record, 28 lks.)

A live oak, 10 ins. diam., bears S. 56° E., 20 lks. dist., with healed blaze.

A live oak, 20 ins. diam., bears S. 27° W., 13 lks. dist., with healed blaze. (Record, S. 36° W.)

and a bearing tree mkd. by the County Surveyor's Office

A live oak, 12 ins. diam., bears N. 47° W., 42 lks. dist., with scribe marks CS S20 visible on partly healed double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, and chinquapin; undergrowth, poison oak, manzanita, hazel, vine maple, and young timber.