

County Surveyor's Record, Douglas County, Oregon

17421

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

41.40

From the cor. of secs. 15, 16, 21, and 22.

N. 87° 53' W., bet. secs. 16 and 21.

Ascend 670 ft. along broken N. slope, through heavy timber and dense undergrowth.

The 1/4 sec. cor. of secs. 16 and 21, perpetuated and recorded by Max H. Hull, Registered Land Surveyor, No. 901, in 1973, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. Hull RS 901, from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears S. 64° W., 9 lks. dist., no marks visible.

A fir snag, 10 ins. diam., bears N. 19° W., 16 lks. dist., with scribe marks 1/4 S BT visible on opened double blaze. (Record, N. 12° W.)

and bearing trees mkd. by Hull

A madrone, 10 ins. diam., bears N. 6 1/2° E., 17 lks. dist., with scribe marks S 1/4 RS 901 BT visible on partly healed double blaze.

A fir, 8 ins. diam., bears S. 57 1/2° E., 3 1/2 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

T 33 S R 7 W
1/4 $\frac{S 16}{S 21}$
1981

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, maple, and chinquapin; undergrowth, poison oak, manzanita, hazel, salal, huckleberry, Oregon grape, and young timber.

From the cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 33 S R 7 W
 $\frac{S 30}{S 31} \mid \frac{S 29}{S 32}$
1969

from which the remaining original bearing trees

A live oak, 9 ins. diam., bears N. 23° E., 38 lks. dist., with healed blaze. (Original record, 41 lks.)

A fir, 26 ins. diam., bears S. 12° W., 15 lks. dist., with healed blaze. (Original record, S. 30° W.)