

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17422**
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 28 ins. diam., bears N. 80° W., 57 lks. dist., with healed blaze. (Original record, N. 78° W.)

and a bearing tree mkd. by Aanrud, Jelley, and Roseberry

A fir, 18 ins. diam., bears S. 63° E., 69 1/2 lks. dist., with scribe mark 3 visible on partly healed blaze.

N. 89° 53' W., bet. secs. 30 and 31.

Ascend 365 ft. over SE slope, changing to E. slope, through heavy timber and dense undergrowth.

15.75 Spur ridge, bears N. 15° E. and S. 15° W., slopes S. 15° W.; desc. 180 ft. over W. slope.

19.955 The E. 1/16 sec. cor. of secs. 30 and 31, established and recorded by Ronald A. Brandt, Registered Land Surveyor, No. 841, in 1981, and is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Brandt

A live oak, 11 ins. diam., bears N. 40 1/4° E., 29 lks. dist., with scribe marks E1/16 S30 PS 841 BT visible on open blaze.

A fir, 22 ins. diam., bears S. 37 1/4° E., 22 lks. dist., with scribe marks E1/16 S31 PS 841 BT visible on open blaze.

A fir, 16 ins. diam., bears S. 26 1/2° W., 37 lks. dist., with scribe marks E 1/16 S31 PS 841 BT visible on open blaze.

A fir, 24 ins. diam., bears N. 40 1/2° W., 17 lks. dist., with scribe marks E1/16 S30 PS 841 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

E 1/16 $\frac{S\ 30}{S\ 31}$
1981

N. 89° 53' W., beginning new measurement.

Descend 570 ft. over steep W. slope.

19.975 The 1/4 sec. cor. of secs. 30 and 31, reestablished at proportionate distance and recorded by Ronald A. Brandt, Registered Land Surveyor, No. 841, in 1981, and is accepted as the best available evidence of the original corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Brandt

A madrone, 8 ins. diam., bears N. 74° W., 28 1/2 lks. dist., with scribe marks 1/4 S30 PS 841 BT visible on open blaze.