

# County Surveyor's Record, Douglas County, Oregon

17423

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears S. 11° W., 11 1/2 lks. dist., with scribe marks 1/4 S31 PS 841 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 33 S    R 7 W  
          1/4  $\frac{S 30}{S 31}$   
                  1981

N. 89° 53' W., beginning new measurement.

Descend 460 ft. over broken NW. slope.

1.00            Abandoned mining ditch, 8 lks. wide, bears NE. and SW.

13.50          Reuben Creek Road, rock surfaced- 15 lks. wide, bears N. 20° E. and S. 20° W.

14.20          Reuben Creek, 40 lks. wide, course S. 30° W.; asc. 225 ft. over E. slope.

19.965        Point for the W. 1/16 sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16  $\frac{S 30}{S 31}$   
                  1981

from which

A fir, 22 ins. diam., bears N. 39 1/4° E., 25 lks. dist., mkd. W1/16 S30 BT.

A fir, 19 ins. diam., bears S. 42 1/2° E., 37 lks. dist., mkd. W1/16 S31 BT.

Ascend 705 ft. over steep E. slope.

39.73          The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, and alder; undergrowth, poison oak, manzanita, hazel, huckleberry, salal, and Oregon grape.

From the cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by the Josephine County Surveyor's Office, in 1976, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR  
T 33 S    R 7 W  
S     $\frac{19 | 20}{30 | 29}$   
          1976