

# County Surveyor's Record, Douglas County, Oregon

**17425**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
1.00	Ridge, bears N. and S., also dirt road, 15 lks. wide, bears same; desc. 635 ft. over W. slope.
20.13	<p>The 1/4 sec. cor. of secs. 19 and 30, reestablished by proportionate measurement and recorded by Ronald A. Brandt, Registered Land Surveyor, No. 841, in 1981, and is accepted as the best available evidence of the original corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Brandt</p> <p style="margin-left: 40px;">A madrone, 6 ins. diam., bears N. 62 1/2° W., 22 lks. dist., with scribe marks 1/4 S19 PS 841 BT visible on open blaze.</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears S. 43° E., 29 lks. dist., with scribe marks 1/4 S30 PS 841 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T 33 S R 7 W</p> <p>1/4 <math>\frac{S 19}{S 30}</math></p> <p>1981</p> </div> <p>N. 89° 47' W., beginning new measurement.</p> <p>Descend 1095 ft. over broken W. slope.</p>
40.39	<p>The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., monumented with a basalt stone, 20 x 12 x 10 ins., firmly set, 12 ins. in the ground, mkd. with 4 notches on the N. and 2 notches on the S. edges, from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir snag, 40 ins. diam., bears N. 50° E., 30 lks. dist., with scribe marks T BT visible on bark blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. 50° E., 9 lks. dist., alongside of which is lying a decayed madrone, size indeterminate, no marks visible on decayed blaze.</p> <p style="margin-left: 40px;">A fir snag, 18 ins. diam., bears S. 12° W., 50 lks. dist., with scribe marks 33S R8W visible on opened blaze. (Record, S. 10° W., 53 lks.)</p> <p style="margin-left: 40px;">A fir snag, 33 ins. diam., bears N. 22 1/4° W., 117 lks. dist., no marks visible on bark blaze. (Record, N. 25° W., 122 lks.)</p> <p>and a bearing tree mkd. by Ronald A. Brandt, Registered Land Surveyor, No. 841</p> <p style="margin-left: 40px;">A live oak, 10 ins. diam., bears S. 50° E., 32 1/2 lks. dist., with scribe marks SC 30 PS 841 BT visible on open blaze.</p> <p>At the corner point</p>