

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17426
 T. 33 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S T 33 S
 R 8 W | S 19
 S 25 | S 30
 R 7 W
 1981

from which a new bearing tree

A madrone, 8 ins. diam., bears N. 65° E., 8 lks. dist., mkd. T33S R7W S19 BT.

Deposit the corner stone alongside the iron post.

From this point, the cor. of secs. 24 and 25 only, on the E. bdy. of T. 33 S., R. 8 W., bears N. 0° 36' E., 0.23 chs. dist., monumented with the original basalt stone, 20 x 16 x 6 ins., loosely set, 8 ins. in the ground, with faint chisel marks visible on N. and S. edges, with an iron pipe, 1 in. diam., firmly set, by person(s) unknown, projecting 4 ins. above ground, alongside, and from which the original bearing trees

A fir, 20 ins. diam., bears S. 39 1/2° W., 77 lks. dist., with healed blaze.

A madrone, 9 ins. diam., bears N. 15° W., 18 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, and chinquapin; undergrowth, poison oak, manzanita, hazel, salal, and Oregon grape.

From the cor. of secs. 17, 18, 19, and 20, perpetuated and recorded by the Josephine County Surveyor's Office, in 1976, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR
 T 33 S R 7 W
 18 | 17
 19 | 20
 1976

from which the remains of the original bearing trees

A sawed sugar pine stump, 35 ins. diam., bears N. 6° E., 122 lks. dist., with healed blaze.

A sawed sugar pine stump, 32 ins. diam., bears S. 58 1/2° E., 140 lks. dist., no marks visible.

A decayed sugar pine stump, 37 ins. diam., bears S. 59° W., 91 lks. dist., with old axe marks visible on decayed blaze.

A sawed sugar pine stump, 50 ins. diam., bears N. 11° W., 181 lks. dist., with healed blaze.

and bearing trees mkd. by the County Surveyor's Office