

County Surveyor's Record, Douglas County, Oregon

17431

T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and subdivision of section 35, Township 26 South, Range 3 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The south and east boundaries of the township and a portion of the subdivisional lines were surveyed by Addison R. Flint, U.S. Deputy Surveyor, in 1855.

A portion of the subdivisional lines was surveyed by Addison R. Flint and L. L. Williams, U.S. Deputy Surveyors, in 1871.

The survey of the subdivisional lines was completed by Samuel C. Flint, U.S. Deputy Surveyor, in 1882.

A portion of the east boundary of the township was resurveyed by Charles M. Collier, U.S. Surveyor, in 1913-14.

A portion of the south boundary of the township was resurveyed by Harold D. Corbin, Cadastral Surveyor, in 1958.

A portion of the subdivisional lines was resurveyed and section 26 was subdivided by Daniel L. Berry, G. Steven Popken, and James J. Carlson, Cadastral Surveyors, in 1972-75.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1058, Oregon, dated April 15, 1981.

The directions of the lines refer to the true meridian, as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming closures were measured twice to preclude error.

The geographic position of the N 1/16 section corner of sections 34 and 35, as determined by a direct tie to Douglas County Surveyors Office horizontal control stations "SNAKE", is as follows:

Latitude 43° 16' 04.89" N. Longitude 123° 01' 44.74" W.

The mean magnetic declination is 18° 15' E.