

# County Surveyor's Record, Douglas County, Oregon

17432

Dependent Resurvey of a Portion of the South Boundary,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

**CHAINS**

(Restoring the survey by Addison R. Flint in 1855  
and the resurvey by Harold D. Corbin in 1958)

Beginning at the 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 26 S    R 3 W  
1/4  $\frac{S 35}{S 2}$   
T 27 S

1958

from which the remains of bearing trees mkd. by Corbin

A fir, 42 ins. diam., bears S. 2 1/2° W., 116 lks. dist., with healed blaze.

A sawed fir stump, 57 ins. diam., bears N. 56 1/2° W., 48 lks. dist., with healed blaze.  
(Record, N. 59 1/2° W.)

and a new bearing tree

A fir, 6 ins. diam., bears N. 2° E., 25 lks. dist., mkd. 1/4 S35 BT.

The corner is located on S. edge of logged area.

N. 89° 33' W., bet. secs. 2 and 35, marking and blazing the true line.

Descend 210 ft. over broken SW. slope, along S. edge of logged area.

6.80      Creek, 2 lks. wide, course S. 75° W.; asc. 10 ft. over broken SE. slope, also enter moderate timber and undergrowth, edge bears N. and E.

19.00      Spur, slopes S.; desc. 50 ft. over SW. slope.

20.46      The W 1/16 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.

W 1/16  $\frac{S 35}{S 2}$

1958

from which bearing trees mkd. by Corbin

A pine, 18 ins. diam., bears N. 27° E., 183 lks. dist., with healed blaze. (Record, N. 20° E.)

A twin oak, 14 ins. diam., bears S. 24° E., 119 lks. dist., with healed blaze. (Record, S. 31 3/4° E.)

N. 89° 36' W., beginning a new measurement.

Descend 230 ft. over broken SW. slope.

14.50      Gravelled road, 25 lks. wide, bears N. 40° W. and S. 40° E.