

County Surveyor's Record, Douglas County, Oregon


17433

Dependent Resurvey, Portion of S. Bdy.,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

20.40

The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.



1958

from which bearing trees mkd. by Corbin

A fir, 38 ins. diam., bears N. 38 3/4° E.,
571 lks. dist., with healed blaze.
(Record, N. 39 3/4° E.)

A twin cedar, 41 ins. diam., bears S. 33 1/2° E.,
425 lks. dist., with healed blaze.
(Record, S. 32 1/2° E.)

A white oak, 18 ins. diam., bears S. 50 1/2° W.,
675 lks. dist., with healed blaze.
(Record, S. 51 1/2° W.)

A white oak, 20 ins. diam., bears N. 67° W.,
295 lks. dist., with healed blaze.
(Record, N. 66° W.)

Land, mountainous.


Soil, rocky clay.

Timber, pine, oak, hemlock, yew, fir, madrone, alder,
ash, cedar, and chinquapin; undergrowth, poison oak,
blackberry, salmonberry, wild rose, Oregon grape, salal,
huckleberry, arrowwood, hazel, fern, and young timber.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Addison R. Flint in 1855,
the survey by Addison R. Flint and L. L. Williams in 1871,
the survey by Samuel C. Flint in 1882,
the resurvey by Harold D. Corbin in 1958, and
the resurvey by Daniel L. Berry, G. Steven Popken, and
James J. Carlson in 1972-75)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy.
of the Tp., monumented with an iron post, 2 1/2 ins. diam.,
firmly set, projecting 4 ins. above ground, with brass cap
mkd.



from which the remains of bearing trees mkd. by Arthur
Boyer, County Surveyor, in 1936