

County Surveyor's Record, Douglas County, Oregon

17435

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 11 ins. diam., bears S. 60 1/2° E., 16 lks. dist., mkd. S 1/16 S36 BT.</p> <p>A cedar, 9 ins. diam., bears S. 82 1/2° W., 10 lks. dist., mkd. S 1/16 S35 BT.</p> <p>Ascend 40 ft. over broken SW. slope.</p>
22.40	Spur, slopes S. 35° W.; desc. 190 ft. over NW. slope.
34.30	Creek, 2 lks. wide, course N. 80° W.; asc. 5 ft. over SW. slope.
34.80	Power transmission line, bears N. 70° E. and S. 70° W.
39.58	<p>The 1/4 sec. cor. of secs. 35 and 36, determined at record bearing and distance from the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed fir stump, 40 ins. diam., bears S. 45° E., 14 lks. dist., with axe marks visible on decayed blaze.</p> <p style="margin-left: 40px;">A decayed fir stump, 24 ins. diam., bears N. 75° W., 45 lks. dist., no marks visible.</p> <p>At the corner point</p> <p style="margin-left: 40px;">Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin-left: 80px;"> <p>T 26 S R 3 W</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 20px;">S 35 S 36</p> <p style="margin-left: 40px;">1981</p> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 24 1/2° E., 8 1/2 lks. dist., mkd. 1/4 S36 BT.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. 87° W., 17 lks. dist., mkd. 1/4 S35 BT.</p> <hr style="width: 20%; margin-left: 40px;"/> <p>N. 0° 48' E., beginning new measurement.</p> <p>Ascend 55 ft. over SW. slope.</p>
5.15	Spur, slopes S. 75° W.; desc. 435 ft. over NW. slope.
20.35	Dirt road, 20 lks. wide, bears N. 85° W. and S. 80° E.
23.35	Gravelled road, 25 lks. wide, bears N. 80° E. and S. 40° W., in curve.
34.60	Engles Creek, 10 lks. wide, course S. 85° W.; asc. 120 ft. over SE. slope.
37.10	Gravelled road, 25 lks. wide, bears N. 80° W. and S. 80° E.
40.78	The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.