

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17436
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE
T 26 S

S 26	S 25
S 35	S 36

R 3 W
1966

from which the remains of the original bearing trees

A fir, 34 ins. diam., bears S. 32° W.,
20 lks. dist., with healed blaze.
(Record, S. 35° W.)

A fir stump, 35 ins. diam., bears N. 30° W.,
32 lks. dist., with healed blaze.

and bearing trees mkd. by Thomas E. Shrum, Registered
Engineer, No. 4287, in 1962

A yew, 12 ins. diam., bears N. 57° E., 41 lks.
dist., with scribe marks S25 BT visible on
open double blaze.

A maple, 10 ins. diam., bears S. 71° E., 70 lks.
dist., with scribe marks S36 BT visible on
open double blaze.

A cedar, 26 ins. diam., bears N. 85° W., 46 lks.
dist., with scribe marks S26 BT visible on
open double blaze.

Land, mountainous.

Soil, rocky clay.

Timber, oak, yew, fir, hemlock, madrone, ash, alder,
cedar, maple, and pine; undergrowth, poison oak, vine
maple, arrowwood, hazel, fern, salmonberry, blackberry,
thimbleberry, huckleberry, Oregon grape, salal, and young
timber.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy.
of the Tp., perpetuated and recorded by Vernon R. Tracy,
Deputy County Surveyor, in 1966, monumented with an iron
post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S

R	S 25	S 30	R
3	S 36	S 31	2
W			W

1966

from which the remaining original bearing tree

A fir, 33 ins. diam., bears S. 45° E., 33 lks.
dist., with illegible scribe marks visible on
opened blaze.

and bearing trees mkd. by Tracy

A fir, 9 ins. diam., bears N. 57° E., 7 lks.
dist., with healed double blaze.

A fir, 11 ins. diam., bears S. 37 1/2° W., 11 1/2 lks.
dist., with healed double blaze.