

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines
T. 26 S., R. 3 W., Willamette Meridian, Oregon **17438**

CHAINS			
11.90	Engles Creek, south channel, 5 lks. wide, course SW.; continue over creek bottom.		
12.25	Engles Creek, north channel, 5 lks. wide, course SW.; asc. 80 ft. over broken SW. slope.		
19.98	<p>The S 1/16 sec. cor. of secs. 34 and 35, established and recorded by Glenn S. Baughman, Registered Land Surveyor, No. 536, in 1975, and is accepted as the corner, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 3 W S 1/16</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> </table> <p>RLS 536 1975</p> </div> <p>from which bearing trees mkd. by Baughman</p> <p style="margin-left: 40px;">A cedar, 10 ins. diam., bears S. 85 3/4° E., 28 lks. dist., with scribe marks S 1/16 S35 BT visible on partially healed double blaze.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 4 3/4° E., 62 lks. dist., with fragmentary scribe marks on partially healed double blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 63 1/4° W., 52 lks. dist., mkd. S 1/16 S34 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3° 47' W., beginning new measurement.</p> <p>Ascend 30 ft. over broken SW. slope.</p>	S 34	S 35
S 34	S 35		
1.95	Spur, slopes W.; desc. 135 ft. over NW. slope.		
8.75	Gravelled road, 25 lks. wide, bears N. 50° E. and S. 40° W.		
12.50	Dry creek bed, 10 lks. wide, drains S. 85° W.; desc. 5 ft. over NW. slope.		
13.40	Ravine, drains S. 50° W.; asc. 10 ft. over SW. slope.		
14.50	Spur, slopes S. 80° W.; desc. 15 ft. over NW. slope.		
15.00	Creek, 2 lks. wide, course S. 80° W.; asc. 120 ft. over S. slope.		
19.97	The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.		