

County Surveyor's Record, Douglas County, Oregon

17439

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 26 S
 1/4 S 34 | S 35
 R 3 W
 1966

from which bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966

A pine, 20 ins. diam., bears N. 13 1/2° E., 106 lks. dist., with healed blaze. (Record, N. 12° E.)

A cedar, 12 ins. diam., bears N. 2° W., 27 lks. dist., with healed blaze.

The corner is located at intersection of wire fences, extending N., S., and W.

Land, mountainous.

Soil, rocky clay.

Timber, pine, cedar, fir, oak, madrone, yew, alder, ash, maple, and hemlock; undergrowth, poison oak, vine maple, blackberry, salmonberry, huckleberry, wild rose, wild plum, arrowwood, manzanita, rhododendron, hazel, Oregon grape, fern, and young timber.

Subdivision of Section 35,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.

N. 0° 02' E., on the N. and S. center line of sec. 35.

Descend 100 ft. over NW. slope, across open logged area.

3.30 Creek, 5 lks. wide, course S. 25° W.; asc. 285 ft. over broken S. slope.

7.15 Enter moderate timber and undergrowth, edge bears N. 70° W. and S. 70° E.

19.95 Point for the center S 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
 S 1/16 | S 35
 C
 1981

from which

A fir, 28 ins. diam., bears N. 32° E., 8 1/2 lks. dist., mkd. C S 1/16 S35 BT.

A fir, 25 ins. diam., bears N. 56 1/2° W., 29 lks. dist., mkd. C S 1/16 S 35 BT.

Ascend 40 ft. over SW. slope.