

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 35,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

17440

CHAINS

- 22.15 Leave timber; enter logged area, edge bears E. and W.
 - 22.60 Gravelled road, 20 lks. wide, bears N. 80° W. and S. 80° E.
 - 23.45 Spur, slopes W.; desc. 230 ft. over NE. slope.
 - 31.15 Enter timber, edge bears E. and W.
 - 34.95 Creek, 1 lk. wide, course N. 50° W.; asc. 15 ft. over SW. slope.
 - 35.65 Spur, slopes N. 75° W.; desc. 15 ft. over NE. slope.
 - 36.50 Creek, 2 lks. wide, course N. 75° W.; desc. 5 ft. over NW. slope.
 - 36.90 Power transmission line, bears N. 80° W. and S. 80° E.
 - 39.90 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 3 W

C 1/4
S 35

1981

from which

A fir, 5 ins. diam., bears S. 15° W., 15 1/2 lks. dist., mkd. C 1/4 S35 BT.

A fir, 5 ins. diam., bears N. 41 1/2° W., 47 lks. dist., mkd. X BT.

Descend 155 ft. over NW. slope.

- 48.75 Engles Creek, 15 lks. wide, course SW.; asc. 330 ft. over steep SE. slope.

- 60.14 Point for the center N 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \\ | \\ N\ 1/16 \quad | \quad S\ 35 \\ | \\ C \end{array}$$

1981

from which

A grand fir, 12 ins. diam., bears S. 22 1/2° E., 15 lks. dist., mkd. CN 1/16 S35 BT.

A fir, 14 ins. diam., bears N. 70 1/2° W., 71 lks. dist., mkd. CN 1/16 S35 BT.

Ascend 155 ft. over broken SE. slope.