

County Surveyor's Record, Douglas County, Oregon

17441

Subdivision of Sec. 35,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
79.30	Gravelled road, 25 lks. wide, bears N. 65° W., and S. 65° E.
80.38	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, with top 4 ins. below surface of ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">1/4 $\frac{S 26}{S 35}$</p> <p style="text-align: center;">1972</p> <p>from which bearing trees mkd. by Berry, Popken, and Carlson</p> <p style="margin-left: 40px;">A cedar, 30 ins. diam., bears N. 47 1/4° E., 86 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, N. 53° E.)</p> <p style="margin-left: 40px;">A cedar, 20 ins. diam., bears S. 83° E., 31 lks. dist., with scribe marks 1/4 S35 BT visible on open blaze.</p> <p>The corner is located on E. edge of dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.</p>
11.00	<p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>N. 89° 39' W., on the E. and W. center line of sec. 35.</p> <p>Descend 170 ft. over SW. slope, through heavy timber and dense undergrowth.</p> <p>Gravelled road, 25 lks. wide, bears N. 30° W. and S. 5° E., in curve.</p>
17.45	Creek, 1 lk. wide, course N. 50° W.; asc. 5 ft. over NE. slope.
18.10	Spur, slopes N. 35° W.; desc. 20 ft. over NW. slope.
19.30	Ravine, drains N. 35° W.; asc. 5 ft. over NE. slope.
19.86	<p>Point for the center E 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E 1/16}{S 35}$ C</p> <p style="text-align: center;">1981</p> <p>from which</p> <p style="margin-left: 40px;">A grand fir, 12 ins. diam., bears N. 19 1/2° E., 11 1/2 lks. dist., mkd. CE 1/16 S35 BT.</p> <p style="margin-left: 40px;">A yew, 14 ins. diam., bears S. 16 1/2° E., 40 1/2 lks. dist., mkd. CE 1/16 S35 BT.</p> <p>Ascend 5 ft. over NE. slope.</p>
20.50	Spur, slopes N. 10° E.; desc. 400 ft. over NW. slope.
21.85	Gravelled road, 25 lks. wide, bears N. 25° E. and S. 25° W.