

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 35,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

17442

CHAINS

39.72

The center 1/4 sec. cor. of sec. 35.

Descend 110 ft. over broken NW. slope.

44.55

Creek, 3 lks. wide, course N. 60° W.; desc. 140 ft. over broken NW. slope.

45.85

Power transmission line, bears N. 75° W. and S. 75° E.

52.95

Engles Creek, 10 lks. wide, course S. 35° W.; asc. 195 ft. over broken SE. slope.

61.48

Point for the center W 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

$$C \frac{W \ 1/16}{S \ 35} C$$

1981

from which

A fir, 10 ins. diam., bears S. 69° W., 73 lks. dist., mkd. C W 1/16 S35 BT.

A fir, 18 ins. diam., bears N. 74° W., 13 lks. dist., mkd. C W 1/16 S35 BT.

Ascend 5 ft. over SE. slope.

63.10

Dirt road, 15 lks. wide, bears N. 55° E. and S. 75° W.

66.15

Spur, slopes S. 30° W.; desc. 335 ft. over NW. slope.

78.70

Ravine, drains S. 55° W.; asc. 15 ft. over SE. slope.

83.24

The 1/4 sec. cor. of secs. 34 and 35.

From the E 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

$$E \ 1/16 \ \frac{S \ 35}{S \ 2}$$

1958

from which the remains of bearing trees mkd. by Corbin

A sawed pine stump, 40 ins. diam., bears N. 0 1/2° E., 137 lks. dist., scribe marks E 1/16 S35 BT visible on partially healed blaze. (Record, 140 lks.)

A fir, 22 ins. diam., bears S. 49° W., 41 lks. dist., with healed blaze. (Record, S. 47 1/4° W.)

and a new bearing tree

A fir, 10 ins. diam., bears N. 27° E., 29 lks. dist., mkd. E 1/16 S35 BT.

N. 0° 46' W., on the N. and S. center line of the SE 1/4 of sec. 35.