

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 35,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

17444

CHAINS	
24.80	Gravelled road, 25 lks. wide, bears N. 75° W. and S. 30° W., in curve.
35.60	Same gravelled road, 25 lks. wide, bears N. 55° W. and S. 80° E.
40.29	The center S 1/16 sec. cor. of sec. 35.
	<p>From the W 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>N. 1° 50' W., on the N. and S. center line of the SW 1/4 of sec. 35.</p> <p>Ascend 80 ft. over broken SW. slope, through scattering timber and moderate undergrowth.</p>
4.50	Spur, slopes S. 20° E.; asc. 70 ft. along spur.
12.75	Spur, slopes S. 5° W.; desc. 20 ft. over broken NW. slope.
19.95	Point for the SW 1/16 sec. cor. of sec. 35.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 35 1981</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 65 1/2° E., 19 lks. dist., mkd. SW 1/16 S35 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 67 1/2° E., 20 lks. dist., mkd. SW 1/16 S35 BT.</p> <p>Descend 190 ft. over NW. slope.</p>
31.50	Engles Creek, 15 lks. wide, course S. 73° W.; asc. 250 ft. over SE. slope.
39.90	The center W 1/16 sec. cor. of sec. 35.
	<p>From the center S 1/16 sec. cor. of sec. 35.</p> <p>N. 89° 36' W., on the E. and W. center line of the SW 1/4 of sec. 35.</p> <p>Descend 5 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
2.85	Head of ravine, drains SW.; asc. 35 ft. over SE. slope.
4.20	Dirt road, 20 lks. wide, bears N. 20° E. and S. 35° W.
6.40	Spur, slopes S. 10° E.; desc. 335 ft. over broken SW. slope.
19.35	Ravine, drains N. 20° W.; asc. 5 ft. over NE. slope.
20.80	Spur, slopes N. 65° W.; desc. 5 ft. over NW. slope.
21.09	The SW 1/16 sec. cor. of sec. 35.