

# County Surveyor's Record, Douglas County, Oregon

17449

T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, Township 31 South, Range 4 West, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the District Manager, Medford, for administrative purposes of the Bureau of Land Management.

The mean magnetic declination is 19° E.

Subdivisions, T. 31 S., R. 4 W.,  
Willamette Meridian, Oregon

(Remonumenting corners established by William M. Bushey,  
U.S. Deputy Surveyor, in 1894)

The cor. of secs. 25, 26, 35, and 36, monumented with the original basalt stone, 10 x 7 x 5 ins. (record, 14 x 11 x 5 ins.), firmly set 5 ins. in the ground, mkd. with 1 notch on E. and 1 notch on S. edges, from which the remains of the original bearing trees and mound of stone:

A burned root crown with white oak sprouts, size indeterminate, bears S. 61 3/4° W., 205 lks. dist.

A fir, 44 ins. diam., bears N. 70 3/4° W., 117 1/2 lks. dist., with scribe marks BT visible on opened and burned blaze.

A mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, bears West, 4 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 31 S	R 4 W
S 26   S 25	
S 35   S 36	
1980	

from which new bearing trees

A fir, 13 ins. diam., bears N. 24 1/2° E.,  
60 1/2 lks. dist., mkd. T31S R4W S25 BT.

A fir, 15 ins. diam., bears S. 26° E.,  
24 lks. dist., mkd. T31S R4W S36 BT.

A fir, 9 ins. diam., bears S. 43 1/2° W.,  
34 1/2 lks. dist., mkd. T31S R4W S35 BT.

A fir, 17 ins. diam., bears N. 26 1/4° W.,  
35 lks. dist., mkd. T31S R4W S26 BT.

Deposit corner stone alongside iron post.