

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points, **17450**
 T. 31 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The 1/4 sec. cor. of secs. 25 and 26, monumented with the original basalt stone, 14 x 12 x 8 ins., loosely set 3 ins. in the ground, mkd. 1/4 on W. face, from which the remains of the original bearing trees:

A fir, 42 ins. diam., bears S. 67 3/4° E.,
 7 1/2 lks. dist., with healed blaze.

A decayed fir stump, 12 ins. diam., bears
 N. 25 3/4° W., 17 lks. dist., with scribe
 marks 1/4 S BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 4 W
 1/4
 S 26 | S 25
 1980

from which a new bearing tree

A fir, 6 ins. diam., bears N. 27° W., 21 lks.
 dist., mkd. 1/4 S26 BT.

Deposit corner stone alongside iron post.

The 1/4 sec. cor. of secs. 26 and 35, monumented with the original basalt stone, 14 x 8 x 6 ins., loosely set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on N. face, from which the remains of the original bearing trees:

A madrone root crown, bears N. 81 3/4° E.,
 5 1/4 lks. dist.

A fir, 43 ins. diam., bears S. 84° W., 59 lks.
 dist., with scribe marks 1/4 S visible on
 partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 4 W
 1/4 S 26
 S 35
 1980

Flood
 6107 Lang
 M 125-6
 4/96

from which a new bearing tree

A fir, 17 ins. diam., bears N. 68° E., 23 lks.
 dist., mkd. 1/4 S26 BT.

Deposit corner stone alongside iron post.