

# County Surveyor's Record, Douglas County, Oregon

17452

T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and subdivision of section 27, Township 20 South, Range 9 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

Portions of the subdivisional lines were surveyed by William Thiel, U.S. Deputy Surveyor, in 1877 and 1891 under two contracts.

A portion of the subdivisional lines was resurveyed by Thomas A. Tillman and Joseph S. Gawron, Cadastral Surveyors, in 1953-54.

Certain original corner points were remonumented without survey by William W. Glenn and James E. Jelley, Cadastral Surveyors, in 1967.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated February 9, 1982, for Group Number 1090, Oregon.

The directions of lines refer to the true meridian as determined by deflection angles from azimuths obtained by direct solar observation.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified, and only the true line field notes are given herein. All lines not forming a closure were measured twice to preclude error. Only those lines bounding or crossing public land were blazed.

The geographic position of the corner of sections 26, 27, 34, and 35, as scaled from the "ROMAN NOSE MTN., OREG.", topographic map, published by the United States Geological Survey in 1942, is as follows:

Latitude 43° 47.9' N. Longitude 123° 44.8' W.

The mean magnetic declination is 21° E.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 20 S., R. 9 W.,  
Willamette Meridian, Oregon

(Restoring the surveys by William Thiel in 1877 and 1891, the resurvey by Thomas A. Tillman and Joseph S. Gawron in 1953-54, and the remonumentation by William W. Glenn and James E. Jelley in 1967)

Beginning at the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, alongside of which is a steel fence post, firmly set, projecting 4 ft. above ground, with brass cap mkd.

T 20 S	R 9 W
S 27	S 26
S 34	S 35
1953	