

# County Surveyor's Record, Douglas County, Oregon

**17455** Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

S. 85° 34' W., bet. secs. 27 and 34.

Descend over gradual SW. slope, through moderate timber and dense undergrowth.

5.35 Smith River Road, asphalt surface, 30 lks. wide, bears N. 15° W. and S. 35° E., in curve.

6.40 Right bank of Smith River, bears N. 15° W. and S. 20° E., course N. 15° W.; thence across river.

7.40 Left bank of Smith River, bears same; asc. over steep E. slope.

18.16 The angle point of secs. 27 and 34, monumented with a root hole, from which the remains of a bearing tree mkd. by Tillman and Gowron:

A fir stump, 15 ins. diam., bears S. 63° E., 34 lks. dist., with scribe marks AP T20S R9W S34 BT visible on an open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock and encircled with a mound of stone, 4 ft. base, to top, with brass cap mkd.

AP  
T 20 S R 9 W  
S 27  
S 34  
1983

from which new bearing trees

A fir, 14 ins. diam., bears S. 19 1/4° E., 254 lks. dist., mkd. AP T20S R9W S34 BT.

A fir, 15 ins. diam., bears N. 29 1/2° W., 93 lks. dist., mkd. AP T20S R9W S27 BT.

The corner point is located on top of a spur, slopes N. 20° W., at edge of timber, bears N. 20° W. and S. 20° E.

S. 89° 54' W., beginning new measurement.

Descend over broken W. slope, across open meadow

1.92 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole, on a rock face, 5 x 5 x 1 ft. above ground, mkd.

E 1/16  $\frac{S 27}{S 34}$   
1983

from which

A fir, 17 ins. diam., bears N. 86 3/4° E., 146 lks. dist., mkd. E 1/16 S27 BT.

A fir, 17 ins. diam., bears S. 46 1/2° E., 97 1/2 lks. dist., mkd. E 1/16 S34 BT.