

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17460**  
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	$W \frac{1}{16} \begin{array}{l} S \ 22 \\ S \ 27 \\ 1982 \end{array}$
	from which
	A fir, 36 ins. diam., bears S. 11 1/2° W., 115 lks. dist., mkd. W 1/16 S27 BT.
	A fir, 26 ins. diam., bears N. 23° W., 72 lks. dist., mkd. W 1/16 S22 BT.
	Continue over nearly level ground.
30.60	Descend over SW. slope.
33.20	Creek, 8 lks. wide, course N. 65° W.; asc. over broken NE. slope.
39.84	The cor. of secs. 21, 22, 27, and 28.
	Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, and maple; undergrowth, vine maple, huckleberry, hazel, salmonberry, arrowwood, salal, and fern.
	From the cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	$T \ 20 \ S \quad R \ 9 \ W \\ \begin{array}{c c} S \ 19 & S \ 20 \\ \hline S \ 30 & S \ 29 \end{array} \\ 1953$
	from which the remains of the original bearing trees
	A decayed fir stump, 40 ins. diam., bears N. 27° E., 39 lks. dist., with fragmentary scribe marks visible on a bark blaze.
	A fir, 64 ins. diam., bears S. 49° W., 75 lks. dist., with illegible scribe marks visible on a bark blaze.
	A fir, 62 ins. diam., bears N. 52° W., 34 lks. dist., with scribe marks 20S R9W visible on a bark blaze.
	and bearing trees mkd. by Tillman and Gawron
	A hemlock, 16 ins. diam., bears N. 5° E., 94 lks. dist., with healed blaze.
	A hemlock, 12 ins. diam., bears S. 55 1/2° E., 17 lks. dist., with healed blaze.
	S. 82° 18' W., bet. secs. 19 and 30.
	Descend over SW. slope, through moderate timber and undergrowth.
3.80	Ravine, drains S.; asc. over SE. slope.
10.00	Spur, slopes S. 10° E.; desc. over SW. slope.