

County Surveyor's Record, Douglas County, Oregon

17463

Subdivision of Section 27,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
32.20	Spur ridge, bears NE. and SW.; continue over nearly level land.
35.03	Descend over broken NW. slope.
39.69	The center 1/4 sec. cor. of sec. 27. Continue descending over broken NW. slope.
44.65	Smith River Road, asphalt surface, 30 lks. wide, bears N. 10° W. and S., in a curve.
45.25	Right bank of Smith River, bears N. 5° W. and S. 5° E., course N. 5° W.; thence across river.
47.00	Left bank of Smith River, bears same; asc. over broken NE. slope.
59.75	Point for the center W 1/16 sec. cor. of sec. 27. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;"> $C \frac{W \ 1/16}{S \ 27} C$ <p>1982</p> </div> from which A hemlock, 13 ins. diam., bears N. 13 1/4° E., 25 lks. dist., mkd. CW 1/16 S27 BT. A hemlock, 20 ins. diam., bears S. 30 1/4° E., 103 lks. dist., mkd. CW 1/16 S27 BT. Ascend over broken NE. slope.
62.60	Spur, slopes N.; desc. over NW. slope.
67.40	Left bank of Smith River, bears N. 10° W. and S. 10° E., course S. 10° E.; thence across river.
69.90	Right bank of Smith River, bears same; asc. over NE. slope.
71.35	Intersection of West Fork Smith River Road, asphalt surface, 30 lks. wide, bears N. 60° W., and Smith River Road, asphalt surface, 30 lks. wide, bears N. 10° E. and S. 10° E.
79.81	The 1/4 sec. cor. of secs. 27 and 28.
	From the center W 1/16 sec. cor. of sec. 27. N. 1° 03' W., on the N. and S. center line of the NW 1/4 of sec. 27. Descend over broken N. slope, through moderate timber and light undergrowth.
13.65	Left bank of Smith River, bears E. and SW., course SW.; thence across river.
16.15	Right bank of Smith River, bears same; continue over nearly level land.
16.80	Smith River Road, asphalt surface, 30 lks. wide, bears same; asc. over broken S. slope.