

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 27,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

17464

CHAINS	
20.55	<p>Point for the NW 1/16 sec. cor. of sec. 27.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 27 1982</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 60° E., 12 lks. dist., mkd. NW 1/16 S 27 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 34 1/2° E., 21 lks. dist., mkd. NW 1/16 S27 BT.</p> <p>Ascend over broken S. slope.</p>
24.60	Top of ascent, slopes S. 70° W.; continue over nearly level spur ridge.
30.60	Descend over N. slope.
40.20	Creek, 4 lks. wide, course W.; asc. over S. slope.
41.10	The W 1/16 sec. cor. of secs. 22 and 27.
	<p>From the center N 1/16 sec. cor. of sec. 27.</p> <p>S. 89° 45' W., on the E. and W. center line of the NW1/4 of sec. 27.</p> <p>Descend over NW. slope, through moderate timber and light undergrowth.</p>
2.35	Creek, 4 lks. wide, course S. 30° W.; asc. over SE. slope.
11.32	Spur, slopes S. 10° E.; desc. over SW. slope.
19.99	The NW 1/16 sec. cor. of sec. 27.
	Continue descending over SW. slope.
23.25	Bottom of descent, slopes S.; asc. over SE. slope.
31.35	Top of ascent, bears NE. and SW.; continue over nearly level land.
39.97	The N 1/16 sec. cor. of secs. 27 and 28.
	<p>GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 17 miles northeasterly of the town of Gardiner, Oregon.</p> <p>Access is by way of U.S. Highway 101 to Smith River Road, which traverses the area resurveyed. The elevation ranges from about 200 feet above sea level along Smith River, to about 1,100 feet above sea level between sections 19 and 30. The area is drained by Smith River which flows westerly and in turn is fed by many small creeks and tributaries.</p>