

County Surveyor's Record, Douglas County, Oregon

17469

Corrective Dependent Resurvey of a Portion of
the West Boundary, T. 19 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS

An alder, 23 ins. diam., bears N. 26° W., 105 lks. dist., with scribe marks S 1/16 visible on the bark.

A twin maple, 40 ins. diam., bears S. 61 3/4° W., 107 lks. dist., with healed blaze.

Continue over nearly level land.

18.70 West Fork of Smith River, 12 lks. wide, course S. 75° E.; asc. along broken W. slope.

26.10 West Fork of Smith River, 10 lks. wide, course SW.; asc. gradually over nearly level land.

32.70 West Fork of Smith River, 10 lks. wide, course S. 20° E.; asc. over SW. slope.

37.75 Top of ascent, slopes W.; desc. over NW. slope.

38.13 Point for the 1/4 sec. cor. of sec. 24 only, T. 19 S., R. 9 W.

From this point, the 1/4 sec. cor. of sec. 24 only, erroneously positioned by Tillman, Holm, and Brooks, bears N. 88° 50' W., 0.039 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. and witnessed as described in the official record.

I remove the iron post, and at the true corner point

Reset the iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T 19 S	
R 9 W	
1/4 S 24	

from which bearing trees mkd. by Tillman, Holm, and Brooks

A hemlock, 16 ins. diam., bears S. 35° W., 98 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 77 ins. diam., bears N. 47° W., 29 lks. dist., with healed blaze.

and new bearing trees

A cedar, 68 ins. diam., bears S. 48 1/2° W., 99 lks. dist., mkd. 1/4 S24 BT.

A maple, 10 ins. diam., bears N. 57° W., 45 lks. dist., mkd. 1/4 S24 BT.

Descend over NW. slope.

39.89 The cor. of secs. 18 and 19 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.